



# PRODUCT SPECIFICATION

## AISCAN TUBCG

TYPE	MATERIAL	COATING	A	B	SHEET METAL THICKNESS	L	PACKING (meters)	PLAIN
								* TUBCG06
AISCAN-TUBCG06 *	METALLIC	HOT DIP GALVANISED	60	18	0,6	3000	6	
AISCAN-TUBCG10	"	"	100	14	0,6	3000	6	
AISCAN-TUBCG15	"	"	150	14	0,6	3000	6	
AISCAN-TUBCG20	"	"	200	14	0,6	3000	6	
AISCAN-TUBCG30	"	"	300	14	0,6	3000	6	
AISCAN-TUBCG40	"	"	400	14	0,6	3000	6	
AISCAN-TUBCG50	"	"	500	14	0,8	3000	6	
AISCAN-TUBCG60	"	"	600	14	0,8	3000	6	
EDITION DATE	EDITION NUMBER	REFERENCE OF DOCUMENT						
2019/08	3	EP-TUBCG						

CHARACTERISTICS ACCORDING TO STANDARD IEC 61537:2007	
DESCRIPTION:	UNIVERSAL COVER
COATING:	HOT DIP GALVANISED IN ACCORDANCE WITH UNE-EN ISO 1461:2010
MATERIAL:	METALLIC
ELECTRICAL CONTINUITY:	YES
FLAME PROPAGATION:	NO
OPERATING TEMPERATURE RANGE:	-50 °C / 150 °C
RESISTANCE TO CORROSION:	CLASS 7
DRILLING LEVEL:	CLASS A
IMPACT RESISTANCE:	20 J TO -40 °C

OBSERVATIONS
VALID FOR BMPG, CMPG AND CMCG. PLUG-IN SYSTEM, WITHOUT SCREWS.
RECOGNIZED AS ACCESSORY SYSTEM ACCORDING TO PARAGRAPH 3.10 OF THE STANDARD UNE-EN 61537:2007.

INSTALLATION FEATURES
THE INSTALLATION OF THIS PRODUCT WILL BE CARRIED OUT ACCORDING TO THE R.E.B.T.