




# PRODUCT SPECIFICATION

## AISCAN TUBCG - CERTIFIED RANGE

TYPE	MATERIAL	COATING	A	B	SHEET METAL THICKNESS	L	PACKING (meters)	PLAIN
AISCAN-TUBCG10C	METALLIC	HOT DIP GALVANISED	100	14	0,8	3000	6	
AISCAN-TUBCG15C	"	"	150	14	0,8	3000	6	
AISCAN-TUBCG20C	"	"	200	14	0,8	3000	6	
AISCAN-TUBCG30C	"	"	300	14	0,8	3000	6	
AISCAN-TUBCG40C	"	"	400	14	0,8	3000	6	
AISCAN-TUBCG50C	"	"	500	14	1	3000	6	
AISCAN-TUBCG60C	"	"	600	14	1	3000	6	
EDITION DATE	EDITION NUMBER	REFERENCE OF DOCUMENT						
2019/08	3	EP-TUBCGC						

CHARACTERISTICS ACCORDING TO STANDARD IEC 61537:2007		OBSERVATIONS	INSTALLATION FEATURES
DESCRIPTION:	UNIVERSAL COVER	VALID FOR BMPG, CMPG AND CMCG. PLUG-IN SYSTEM, WITHOUT SCREWS.	THE INSTALLATION OF THIS PRODUCT WILL BE CARRIED OUT ACCORDING TO THE R.E.B.T.
COATING:	HOT DIP GALVANISED IN ACCORDANCE WITH UNE-EN ISO 1461:2010		
MATERIAL:	METALLIC	RECOGNIZED AS ACCESSORY SYSTEM ACCORDING TO PARAGRAPH 3.10 OF THE STANDARD UNE-EN 61537:2007.	
ELECTRICAL CONTINUITY:	YES		
FLAME PROPAGATION:	NO		
OPERATING TEMPERATURE RANGE:	-50 °C / 150 °C		
RESISTANCE TO CORROSION:	CLASS 7		
DRILLING LEVEL:	CLASS A		
IMPACT RESISTANCE:	20 J TO -40 °C		